

Технический паспорт продукта

Запорный элемент



Ссылочный номер

DAS 4370

Запорный элемент

The motorised locking unit serves for the mechanical door lock. It prevents an unintended entering of armed security areas.

Can be cascaded for several doors.

Features:

- Robust housing of plastics and stainless steel
- Electrical and mechanical emergency operation
- Low noise
- Low stand-by current
- Integrated magnetic contact
- Acknowledge of the bolt position
- To be controlled with static or dynamic signals
- Simple adaption to the door frame
- One magnet and two counterparts are included in the delivery.

To be integrated into the signalling system of the Smart Panels by the KNX system via switching actuators (inputs and emergency opening) or via binary inputs / push-button interfaces (evaluation of the locking unit outputs and the integrated magnetic contacts) respectively.

Supply voltage 12 V DC, separate power supply

Технические характеристики

Номинальное напряжение:	7 ... 15 V DC
Потребляемый ток	
at rest:	около 40 mA
Locking:	макс. 60 mA
Блокировка:	макс. 120 mA
Permissible load of feedback outputs:	50 mA
Bolt way:	12 m
Max. distance to counterpart:	8 mm
Closing / opening time:	< 0,5 s
Permissible shearing force (at 8 mm distance to lock plate):	0,75 kN
Рабочая температура:	-25 ... +60 °C
Температура хранения:	-40 ... +70 °C
длина кабеля:	макс. 3,5 м
Размер	
Корпус (ШxВxГ):	29 x 134 x 28 мм
Stainless steel lock plate (W x H x D):	20 x 175 x 2 mm
Counterpart 1 (Ø x Length):	около 16 x 19 мм
Counterpart 2 (Ø x length):	около 20 x 22 мм
Магнит	около 8 x 30 мм