

Технический паспорт продукта

Комплект проводов базовый



| | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Ссылочный номер | |
| KSB 4 | |
| Комплект проводов | |
| <p>For the connection of the uninterruptible KNX power supply and the lead gel battery the 4-wire cable set (for one battery) must be used. For two batteries the 4-wire and the 2-wire set must be used.</p> <p>The 4-wire cable set has an integrated fuse and a temperature sensor, the 2-wire cable set has only an integrated fuse.</p> | |
| Технические характеристики | |
| Провод | |
| Wires: | 4-wire cable |
| Cross-section: | 0,75 мм ² |
| длина: | 2 м |
| Colour battery connection: | красный: позитивный (12 В аккумулятор) чёрный: отрицательный (GND аккумулятор) |
| Colour temperature sensor: | white: positive (12 V temp. sensor) yellow: negative (GND temp. sensor) |
| Терминалы | |
| Battery connection: | for the connection to the uninterruptible power supply ferrules for the connection to the battery cable lug (6.3 x 0.8 mm) |
| Temperature sensor: | ferrules |
| Вид предохранения: | exchangeable fuse with in-line fuse holder (screw cap) |
| Тип предохранителя: | 5 x 20 мм, T6.3 H 250 В |
| Исполнение: базовый | |